

Aspire Bullnose Corner Paver

Description:

The Aspire Bullnose Corner Paver forms a 90° angle and is designed to fit into the Grid like normal “field” pavers. It is compatible with the Bullnose with Legs to form a border with a rounded edge that hides the grid below.

Benefits:

- Eliminates the need to cut four Bullnose Pavers in the field to create a corner
- Provides a better finished look
- Legs fit into the grid and provide a more secure border
- Hides the side of the Aspire Grid
- Compatible with Aspire Resurfacing Pavers


Physical Properties

Property	Value
Dimensions	9" width X 9" length x 1.6875" thick
Weight	2.5 lbs.
Height with Grid	1.75"
Colors	Available Standard and Premium Colors

Specification	Test Method	Result
Fire Classification	ASTM E108-007	Class A
2" Hail Impact	UL-2218	Class 4
Compression Strength	ASTM C140-09 Section 7	3521 PSI
Flexural Modulus	ASTM C140-09	3842 PSI
Water Absorption	ASTM C67 Section 8	4.10%
Freeze-Thaw	ASTM C67 Section 9	Pass: No sign of cracking or disintegration
Freeze-Thaw Cycling	ASTM C67	Pass
Specific Gravity	FSBP Test Method	0.9
Coefficient of Friction with Pull Monitor	ASTM C1028-07	Wet: 0.47 Dry: 0.83
Chemical Resistance	ASTM F925	No dulling, color change, or surface attack