

Aspire Bullnose Paver – Legless

Description:

The Aspire Bullnose Paver is designed to fit on top of the Aspire patented grid at the perimeter of a layout to cover the side of the grid and provide an attractive rounded edge. It is commonly used on rooftop balconies where there is an exposed edge under a railing. It can also be used on steps or to provide a border for any application.

Benefits:

- Compatible with Aspire Resurfacing Pavers
- Provides an attractive rounded edge
- Hides the side of the Aspire Grid
- Legless design enables it to be attached where needed on the Grid
- Side tabs allow fastening to the Grid along with recommended adhesive between the bottom of the Bullnose and Grid



Physical Properties

Property	Value
Dimensions	4" width x 8" length (Grid Coverage 4"x7")
Weight	14 oz
Height with Grid	1.75"
Colors	Available in all Classic and Designer colors

Specification	Test Method	Result
Fire Classification	ASTM E108-007	Class A
2" Hail Impact	UL-2218	Class 4
Compression Strength	ASTM C140-09 Section 7	3521 PSI
Flexural Modulus	ASTM C140-09	3842 PSI
Water Absorption	ASTM C67 Section 8	4.10%
Freeze-Thaw	ASTM C67 Section 9	Pass: No sign of cracking or disintegration
Freeze-Thaw Cycling	ASTM C67	Pass
Specific Gravity	FSBP Test Method	0.9
Coefficient of Friction with Pull Monitor	ASTM C1028-07	Wet: 0.47 Dry: 0.83
Chemical Resistance	ASTM F925	No dulling, color change, or surface attack